

D-Connectors, Filtered

Tin Plated Shells



D-Connectors with machine tooled or stamped contacts and capacitor filtering (standard 1000 pF). Quality level 3 is standard. These filter connectors are available with solder cup, dip solder and wire wrap terminals. All models have tin plated shells.

Glass-filled PBT, UL 94V-0 Material : Contacts : Copper Alloy Plating Gold over Nickel : Electrical : See Chapter 15

Other capacities on request.

Solder cup model



09 to 37 circuits Male models are 0.40mm higher.

■ Cable solder model.



09 to 37 circuits Male models are 0.40mm higher.

PCB solder model, straight.





Tel +31-(0)497-386878* ÷ Fax +31-(0)497-386888* ŝ, kontakt@interkontakt.com E-mail 11



DFM-XXDS-0022 DFF - XXDS-0022

male, machine tooled contacts female, machine tooled contacts

available circuit sizes: 09, 15, 25, 37

ORDERING INFORMATION

ORDERING INFORMATION

DFM-XXHS-0022

DFF - XXHS-0022

male, stamped contacts

available circuit sizes:

09, 15, 25, 37

female, stamped contacts



Wire wrap model.



■ Right angle model, 10.30mm footprint.



09 to 37 circuits Required hole size for locking clip or mounting hole is Ø3.10mm.



50 circuits

DFM-XXDS-XX22	male, machine tooled contacts
DFF-XXDS-XX22	
	female, machine tooled contacts
	05 MO with couth strip
	— 35 = M3 with earth strip
	36 = M3 with earth strip and locking cli
	38 = UNC 4-40 with earth strip
	39 = UNC 4-40 with earth strip and
	locking clip
	available circuit sizes:
	09, 15, 25, 37, 50



+31-(0)497-386878* 2 +31-(0)497-386888* Fax 2 kontakt@interkontakt.com E-mail 1

Tel

