

## Plastic Circular Connectors, IP 66/68

## 02 to 08 Circuits



■ Lockable cable connector with female contacts\_

Superior leakage protection. Contact area is double sealed for excellent moisture and chemical resistance. Gaskets are moulded onto connector and panel housings to prevent leakage and eliminate the need for additional gaskets. Molded on gaskets reduce part count and assembly labor cost.

Material : Thermoplastic Polymer Glass-Fiber and Thermoplastic Rubber Contacts : Copper Base Alloy Plating : Gold over Nickel

Electrical : See Chapter 15

- 40.10 16.30 UNIC INFORMATION ORD XHS-0000 with solder bucket contacts (AWG 20 max.) available circuit sizes: closed entry contact system 02, 03, 04, 05, 06, 07, 08 Icator boot provides cable strain relief and sealing cable clamps with living hinges "O"-ring mold 02 and 03 circuit models are also available with contacts suitable for AWG 16. Change last four digits of order number to 1000. Lockable cable connector with male contacts The 40.10 16.30 OBJ NFORMATION CPM-XXHS-0000 with solder bucket contacts (AWG 20 max.) available circuit sizes: 02, 03, 04, 05, 06 cato boot provides cable strain relief and sealing cable clamps with living hinges "O"-ring mol 02 and 03 circuit models are also available with contacts suitable for AWG 16. Change last four digits of order number to 1000.
- In-line cable connector with female contacts



Tel

Fax

E-mail

÷

ŝ

1

+31-(0)497-386878\*

+31-(0)497-386888\*

kontakt@interkontakt.com



## Plastic Circular Connectors, IP 66/68 02 to 08 Circuits

## Line connector with male contacts.



Panel mount connector with female contacts



Panel mount connector with male contacts



02 and 03 circuit models are also available with contacts suitable for AWG 16. Change last four digits of order number to 1000.

