



Circular Clearance Spacers


Brass, Aluminium, Polystyrol, Makrolon and Polyamide



A wide range of circular clearance spacers. All indicated lengths are available as standard. Other dimensions are available on request with a M.O.Q. of 5000pcs.

Materials : Nickel Plated Brass
Aluminium
Polystyrol 70 °C (Black)
Makrolon 135 °C (Grey)
Polyamide 110 °C (Black)

■ Brass




ORDERING INFORMATION

SPC-32CC-0000-XX	I.D. = 3.20mm, O.D. = 6.00mm
SPC-33CC-0000-XX	I.D. = 3.30mm, O.D. = 4.80mm
SPC-43CC-0000-XX	I.D. = 4.30mm, O.D. = 8.00mm
SPC-44CC-0000-XX	I.D. = 4.40mm, O.D. = 6.40mm
SPC-53CC-0000-XX	I.D. = 5.30mm, O.D. = 10.00mm

available lengths: (L = mm)
02, 03, 04, 05, 06, 07, 08, 09, 10, 11,
12, 13, 14, 15, 18, 20, 25, 30

■ Aluminium




ORDERING INFORMATION

SPC-32CC-0020-XX I.D. = 3.20mm, O.D. = 5.00mm

available lengths: (L = mm)
03, 04, 05, 06, 07, 08, 09, 10, 11, 12,
13, 14, 15, 18, 20, 25, 30

■ Polystyrol



ORDERING INFORMATION

SPC-36CC-0050-XX	I.D. = 3.60mm, O.D. = 7.00mm
SPC-45CC-0050-XX	I.D. = 4.50mm, O.D. = 8.00mm
SPC-55CC-0050-XX	I.D. = 5.50mm, O.D. = 10.00mm
SPC-62CC-0050-XX	I.D. = 6.20mm, O.D. = 10.00mm

available lengths: (L)
02 = 2.00mm (min.)
35 = 35.00mm (max.)


Available in increments of 1.00mm.



Circular Clearance Spacers

Brass, Aluminium, Polystyrol, Makrolon and Polyamide

■ Makrolon




ORDERING INFORMATION

SPC-36CC-0060-XX	I.D. = 3.60mm, O.D. = 7.00mm
SPC-45CC-0060-XX	I.D. = 4.50mm, O.D. = 8.00mm
SPC-55CC-0060-XX	I.D. = 5.50mm, O.D. = 10.00mm
SPC-62CC-0060-XX	I.D. = 6.20mm, O.D. = 10.00mm

available lengths: (L)
02 = 2.00mm (min.)
35 = 35.00mm (max.)

Available in increments of 1.00mm.

■ Polyamide



ORDERING INFORMATION

SPC-22CC-0070-XX	I.D. = 2.20mm, O.D. = 4.00mm
SPC-27CC-0070-XX	I.D. = 2.70mm, O.D. = 5.00mm
SPC-34CC-0070-XX	I.D. = 3.40mm, O.D. = 6.00mm
SPC-42CC-0070-XX	I.D. = 4.20mm, O.D. = 8.00mm
SPC-52CC-0070-XX	I.D. = 5.20mm, O.D. = 10.00mm
SPC-62CC-0070-XX	I.D. = 6.20mm, O.D. = 10.00mm

available lengths: (L)
02 = 2.00mm (min.)
35 = 35.00mm (max.)

Available in increments of 1.00mm.