



Flexible Multi-Conductor Data Cables


Conductors 0.14mm²/0.25mm²/0.34mm²



A range of flexible multi conductor cables, standard or as twisted pair, with or without copper braided shielding. Conductors are colour coded in accordance with the DIN 47100 specifications.

For more technical data, see chapter 15.

■ Unshielded



ORDERING INFORMATION

MCU-XXST-0140 conductors 0.14mm (standard)²
MCU-XXST-0250 conductors 0.25mm²
MCU-XXST-0340 conductors 0.34mm²

available number of conductors:
(see dimension chart)

■ Shielded



ORDERING INFORMATION

MCS-XXST-0140 conductors 0.14mm²
MCS-XXST-0250 conductors 0.25mm²
MCS-XXST-0340 conductors 0.34mm²

available number of conductors:
(see dimension chart)

■ Available circuit sizes and O.D. dimensions

Cable Model No.	XX = Circuit Sizes																				
	02	03	04	05	06	07	08	10	12	14	15	16	18	20	21	24	25	28	30	32	36
MCU-XXST-0140	3.20	3.40	3.70	4.00	-	4.70	5.30	5.60	5.80	6.10	-	6.40	-	7.10	7.50	-	8.00	8.70	8.70	-	9.30
MCU-XXST-0250	3.60	3.80	4.10	4.50	-	5.40	6.10	6.40	6.60	6.90	-	7.30	7.70	8.20	-	-	9.60	-	9.90	10.30	10.70
MCU-XXST-0340	4.20	4.50	4.90	5.60	-	6.60	7.20	7.60	7.90	8.70	-	9.20	-	10.20	10.80	-	11.50	-	12.30	12.80	13.20
MCS-XXST-0140	3.80	4.00	4.50	4.90	-	5.20	6.00	6.30	6.50	6.70	7.10	7.20	7.40	7.90	8.30	-	9.40	9.40	9.40	9.70	10.10
MCS-XXST-0250	4.30	4.50	4.80	5.40	-	6.30	6.80	7.10	-	7.60	8.00	8.00	9.00	9.50	9.80	-	10.40	10.60	10.60	11.00	11.40
MCS-XXST-0340	4.90	5.40	5.80	6.30	-	7.30	7.90	8.90	9.20	9.60	9.90	9.90	10.30	10.90	11.50	-	12.80	13.20	13.20	13.70	14.10