



# Shrinkable Tubing


## Shrink Ratio 2:1




A program of heat shrinkable tubing, for electric insulation, corrosion protection, cable bundling etc.

Shrink ratio : 2:1  
Flamability : Self-extinguishing  
Operating Temp. : -75°C/+135°C  
Specifications : UL 224 125°C VW1  
MIL-I 23053/5 class 2 and 3  
Shrinking Temp. : >100°C

### ■ KRK series



Before Crimping



After Crimping

#### ORDERING INFORMATION

KRK-XXXX-1000 colour: black  
KRK-XXXX-1008 colour: transparent

available sizes:

0012, 0016, 0024, 0032, 0040, 0064,  
0095, 0127, 0191, 0254, 0320, 0381,  
0508

Shrinkable tubing will be supplied in lengths of 1.00 metre.  
Tubing can be supplied on reels on request. All sizes can also be  
supplied in specified lengths (M.O.Q. 1000pcs).  
After the order number, add two digits to indicate the length in mm.

Example: KRK-0016-1000-07 = shrinkable tubing I.D. 1.60mm,  
length 7mm, colour black.

Other available colours: white, red, blue, yellow and green/yellow.  
All these colours are subject to M.O.Q.

#### DIMENSIONS

| Diameter before crimping (mm) | Diameter after crimping (mm) | Wall thickness (mm) | Reel Size |     |
|-------------------------------|------------------------------|---------------------|-----------|-----|
|                               |                              |                     | R1        | R2  |
| 1.20                          | 0.60                         | 0.40                | 200       | 100 |
| 1.60                          | 0.80                         | 0.43                | 200       | 100 |
| 2.40                          | 1.20                         | 0.51                | 200       | 100 |
| 3.20                          | 1.60                         | 0.51                | 200       | 100 |
| 4.80                          | 2.40                         | 0.52                | 200       | 100 |
| 6.40                          | 3.20                         | 0.65                | 150       | 75  |
| 9.50                          | 4.70                         | 0.65                | 150       | 75  |
| 12.70                         | 6.40                         | 0.65                | 100       | 50  |
| 19.10                         | 9.50                         | 0.77                | 50        | 25  |
| 25.40                         | 12.70                        | 0.89                | 50        | 25  |